

# 094101 GOLDEN TOP PLUS ALU

A versatile and lightweight full body harness for work involving suspension.

With 5 attachment points:  
2 front, 1 back and 2 side

Aluminium alloy components for improved lightweight. Speedy Alu buckles on the leg-loops.

Maximum user's weight: 150 kg


CE EN 358 - EN361 - EN813

ROPE ACCESS

PYLONS/INDUSTRY




1600



| SIZE    | B (cm) | C (cm) | D (cm) |
|---------|--------|--------|--------|
| 1 S-L   | 70-110 | 45-65  | 55-75  |
| 2 L-XXL | 80-130 | 55-75  | 65-85  |

● = Fall arrest attachment element

● = Attachment element for work positioning



High strength polyester webbing 44 mm

Comfortable crossing plate

Aluminium alloy Screwgate connector  
Strength: 22 kN

Aluminium alloy Screwgate connector  
Strength: 24 kN

Forged aluminium alloy positioning D-ring

Belt and leg-loops padded with 3D mesh for best comfort and transpirability

CE label including serial number

Gear-loops with protective plastic tube

Steel gear-rings

Speedy Alu automatic buckles

Reinforced webbings

### NEW PATENT!

Attachment system between the chest and waist that allows the user to attach and detach the connector quickly and easily

